

PRODUCT FOCUS

DIMMAX & DIMMAX FLOOD

Compact Fluorescent Lamp

FOR >> TABLE & FLOOR LAMPS
 >> TRACK & RECESSED LIGHTING
 >> CEILING FIXTURES
 >> HANGING PENDANT



MLS20EADWW/SP
MLS20EADWW

MLS15EADWW/SP★
MLS15EADWW★

MLS25EADWW/SP★
MLS25EADWW★



SKR315FLDWW

★ ENERGY STAR® qualified



- Continuous dimming down to 20%
- Air-gap, amalgam technology, heat sink, and higher temperature (130°C) rated components for greater heat tolerance
- Automatic shut-off function protects lamp
- Works with existing incandescent dimming controls
- Long life - lasts up to 10,000 hours

PRODUCT FOCUS **DIMMAX & DIMMAX FLOOD**
Compact Fluorescent Lamp



MLS15EADWW/SP★

6,000 Hour
(7) 6762701505 (2)*

MLS20EADWW/SP

10,000 Hour
(7) 6762702005 (6)*

MLS25EADWW/SP★

6,000 Hour
(7) 6762701105 (4)*

SKR315FLDWW★

6,000 Hour
(7) 6762733011 (7)*

MLS15EADWW★

6,000 Hour
(7) 6762701504 (5)*

MLS20EADWW

10,000 Hour
(7) 6762702004 (9)*

MLS25EADWW★

6,000 Hour
(7) 6762701104 (7)*

DIMMAX SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 15	01505	MLS15EADWW/SP Dimm. Single Pack	60	900	6,000	Card	18	2.2 x 5.0	2700
★ 15	01504	MLS15EADWW Dimmable	60	900	6,000	Box	12	2.2 x 5.0	2700
20	02005	MLS20EADWW/SP Dimm. Single Pack	75	1200	10,000	Card	12	2.2 x 5.6	2700
20	02004	MLS20EADWW Dimmable	75	1200	10,000	Box	12	2.2 x 5.6	2700
★ 25	01105	MLS25EADWW/SP Dimm. Single Pack	100	1600	6,000	Card	12	2.2 x 5.6	2700
★ 25	01104	MLS25EADWW Dimmable	100	1600	6,000	Box	12	2.2 x 5.6	2700
15	33011	SKR315FLDWW BR30 Dimmable Flood	65	600	6,000	Box	12	3.7 x 5.6	2700

SPECIAL NOTES

>> All DimMax and DimMax Floods dim with existing incandescent dimmers

APPLICATIONS

- Table & floor lamps
- Hanging pendant
- Ceiling fixtures
- Track & recessed Lighting

LOCATIONS

- Residential
- Restaurant
- Retail
- Kitchen
- Hotel/Motel
- Office
- Restaurant

BENEFITS

- Continuous dimming down to 20%
- Air-gap, amalgam technology, heat sink, and higher temperature (130°C) rated components for greater heat tolerance
- Automatic shut-off function protects lamp
- Works with existing incandescent dimming controls
- Long life - lasts up to 10,000 hours

SPECIFICATIONS

- End of Life Ballast >> Yes
- Ballast Type >> Electronic
- Starting Method >> Modified Rapid Start
- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Mini. Starting Temp. >> 0°F
- Max. Operating Temp. >> 100°F
- Color Rendering Index >> 84

MAX6096



FCC Certified
ISO 9002 Certified

* UPC Codes
★ ENERGY STAR® qualified