

PRODUCT FOCUS

# PARs & Rs

Compact Fluorescent Flood Lamp

**FOR >> RECESSED CANS & HIGH HATS  
>> CEILING MOUNTED STRIP LIGHTING**



SKR315FLWW★  
SKR315FLDL  
SKR315FLCW  
SKR315FLWWPD★  
SKR315FLCWPD  
SKR315FLDLPD



SKR423FLWW★  
SKR423FLDL  
SKR423FLWWPD★  
SKR423FLCWPD  
SKR423FLDLPD



SKR3820FLWW★  
SKR3820FLWWPD★



SKR3823FLWW  
SKR3823FLDL  
SKR3823FLWWPD  
SKR3823FL30PD

★ ENERGY STAR® qualified



- Fits flush with standard recessed can fixtures
- Same size and shape as incandescent lamps
- Long life, 8,000 hours; saves up to 75% in energy costs
- Par lamps suitable for indoor/outdoor use
- Frosted glass on R20, R30, and R40 for softer lighting

PRODUCT FOCUS

# PARs & Rs

Compact Fluorescent Flood Lamp



## R LAMPS

<b>SKR207FLWW</b> 8,000 Hour (7) 6762707007 (5)*	<b>SKR315FLWW★</b> 8,000 Hour (7) 6762733015 (5)*	<b>SKR423FLWW★</b> 8,000 Hour (7) 6762733023 (0)*
<b>SKR211FLWW</b> 8,000 Hour (7) 6762707011(2)*	<b>SKR315FLCW</b> 8,000 Hour (7) 6762733019 (3)*	<b>SKR423FLCW</b> 8,000 Hour (7) 6762733030 (8)*
	<b>SKR315FLDL</b> 8,000 Hour (7) 6762733019 (3)*	

## PAR LAMPS

<b>SKR2009FLWW</b> 8,000 Hour (7) 6762711197 (6)*	<b>SKR3015FLWW</b> 8,000 Hour (7) 6762733010 (0)*	<b>SKR3820FLWW★</b> 8,000 Hour (7) 6762733032 (2)*	<b>SKR3823FLWW</b> 8,000 Hour (7) 67627233016 (2)*
<b>SKR2009FLDL</b> 8,000 Hour (7) 6762711199 (0)*	<b>SKR3015FLDL</b> 8,000 Hour (7) 6762733020 (9)*		<b>SKR3823FLDL</b> 8,000 Hour (7) 6762711150 (1)*

## R LAMP SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
7	07007	SKR207FLWW R20 FloodMax	30	245	8,000	Box	25	2.5 x 5	2600
11	07011	SKR211FLWW R20 FloodMax	40	400	8,000	Box	25	2.5 x 5	2700
★ 15	33015	SKR315FLWW R30 FloodMax	75	580	8,000	Box	12	3.75 x 5.6	2700
15	33031	SKR315FLCW R30 FloodMax <b>Cool White</b>	75	580	8,000	Box	12	3.75 x 5.6	4100
15	33019	SKR315FLDL R30 FloodMax <b>Daylight</b>	75	580	8,000	Box	12	3.75 x 5.6	5000
★ 23	33023	SKR423FLWW R40 FloodMax	100	1100	8,000	Box	12	5 x 6	2700
23	33030	SKR423FLCW R40 FloodMax <b>Cool White</b>	100	1100	8,000	Box	12	5 x 6	4100

## PAR LAMP SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
9	11197	SKR2009FLWW Par20 Indoor/Outdoor	60	425	8,000	Box	12	2.45 x 3.8	2700
9	11199	SKR2009FLDL Par20 Indoor/Outdoor	60	425	8,000	Box	12	2.45 x 3.8	5000
15	33010	SKR3015FLWW Par30 Indoor/Outdoor	75	650	8,000	Box	12	3.75 x 5.6	2700
15	33020	SKR3015FLDL Par30 In-Outdoor <b>Daylight</b>	75	650	8,000	Box	12	3.75 x 5.6	5000
★ 20	33032	SKR3820FLWW Par38 Indoor/Outdoor	75	900	8,000	Box	12	5 x 6.2	2700
23	33016	SKR3823FLWW Par38 Indoor/Outdoor	100	1200	8,000	Box	12	5 x 6.2	2600
23	11150	SKR3823FLDL Par38 In-Outdoor <b>Daylight</b>	100	1200	8,000	Box	12	5 x 6.2	5000

MAX6055



FCC Certified  
ISO 9002 Certified  
UPC Codes  
★ ENERGY STAR® qualified



Perma Disk

PRODUCT FOCUS **PARs & Rs**

Compact Fluorescent Flood Lamp



<b>SKR315FLWWD*</b> 8,000 Hour (7) 6762734010 (9)*	<b>SKR423FLWWD*</b> 8,000 Hour (7) 6762733022 (3)*	<b>SKR2009FLWWD</b> 8,000 Hour (7) 6762711198 (3)*	<b>SKR3015FLWWD</b> 8,000 Hour (7) 6762711188 (4)*	<b>SKR3820FLWWD*</b> 8,000 Hour (7) 6762711189 (1)*	<b>SKR3823FLWWD</b> 8,000 Hour (7) 6762711190 (7)*
<b>SKR315FLCWD</b> 8,000 Hour (7) 6762733014 (8)*	<b>SKR423FLCWD</b> 8,000 Hour (7) 6762733026 (1)*		<b>SKR3015FL30PD</b> 8,000 Hour (7) 6762733033 (9)*		<b>SKR3823FL30PD</b> 8,000 Hour (7) 6762733034 (6)*
<b>SKR315FLDLPD</b> 8,000 Hour (7) 6762734020 (8)*	<b>SKR423FLDLPD</b> 8,000 Hour (7) 6762734040 (6)*				

**R LAMP PERMA DISK SPECIFICATIONS**

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 15	34010	SKR315FLWWD R30 with disk	75	580	8,000	Box	12	3.75 x 5.6	2700
15	33014	SKR315FLCWD R30 w/disk <i>Cool White</i>	75	580	8,000	Box	12	3.75 x 5.6	4100
15	34020	SKR315FLDLPD R30 w/disk <i>Daylight</i>	75	580	8,000	Box	12	3.75 x 5.6	5000
★ 23	33022	SKR423FLWWD R40 with disk	100	1100	8,000	Box	12	5 x 6	2700
23	33026	SKR423FLCWD R40 w/disk <i>Cool White</i>	100	1100	8,000	Box	12	5 x 6	4100
23	34040	SKR423FLDLPD R40 w/disk <i>Daylight</i>	100	1100	8,000	Box	12	5 x 6	5000

**PAR LAMP PERMA DISK SPECIFICATIONS**

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
9	11198	SKR2009FLWWD Par20 with disk	60	425	8,000	Box	12	2.45 x 3.8	2700
15	11188	SKR3015FLWWD Par30 with disk	75	650	8,000	Box	12	3.75 x 5.6	2700
15	33033	SKR3015FL30PD Par30 with disk	75	650	8,000	Box	12	3.75 x 5.6	3000
★ 20	11189	SKR3820FLWWD Par38 with disk	75	900	8,000	Box	12	5 x 6.2	2700
23	11190	SKR3823FLWWD Par38 with disk	100	1200	8,000	Box	12	5 x 6.2	2600
23	33034	SKR3823FL30PD Par38 with disk	100	1200	8,000	Box	12	5 x 6.2	3000

SPECIAL NOTES	APPLICATIONS	LOCATIONS
>> Uses amalgam advanced technology for higher lumen maintenance and consistent color.	<ul style="list-style-type: none"> <li>Recessed cans &amp; high hats</li> <li>Ceiling mounted strip lighting</li> <li>Outdoor</li> </ul>	<ul style="list-style-type: none"> <li>Residential/Office/Retail</li> <li>Hotel/Motel/Restaurant</li> <li>School/Hospital/Property Management</li> </ul>

BENEFITS	SPECIFICATIONS
<ul style="list-style-type: none"> <li>Same size and shape as incandescent lamps</li> <li>Fully flush with standard high hat or recessed can applications</li> <li>Par lamps suitable for indoor/ outdoor use</li> <li>Patented Air-Gap on 30/40 guarantees longer life in hot locations</li> <li>Frosted glass on R20/30/40 generates softer, natural lighting</li> </ul>	<ul style="list-style-type: none"> <li>Ballast Type &gt;&gt; Electronic</li> <li>Starting Method &gt;&gt; Modified Rapid Start</li> <li>Input Line Voltage &gt;&gt; 120VAC</li> <li>Input Line Frequency &gt;&gt; 50/60HZ</li> <li>Mini. Starting Temp. &gt;&gt; 0°F</li> <li>Max. Operating Temp. &gt;&gt; 100°F</li> <li>Color Rendering Index &gt;&gt; 84</li> </ul>